

Dow Corning[®] Primer C Construction Sealant Primer

FEATURES

- Nonstaining silane primer for construction applications
- Moisture cure
- Accelerated adhesion to polyvinylidene fluoride (PVF2)- or Kynar-based paints
- Accelerated adhesion to polyester powder paints
- Primer for plastics

Solvent-based silane adhesion promoter for polyvinylidene fluoride (PVF2)- or Kynar[®]-based paints and other plastic surfaces

APPLICATIONS

- Accelerated adhesion of *Dow Corning*[®] 983 Structural Glazing Sealant, *Dow Corning*[®] 993 Structural Glazing Sealant and *Dow Corning*[®] 993N Structural Glazing Sealant to polyvinylidene fluoride (PVF2)- or Kynar-based paints
- Adhesion promotion to plastic surfaces

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Property	Unit	Result
Coverage Rate, nonporous substrates	ft ² /gal	800
Lineal Coverage Rate, 1/2" wide joint	ft/gal	10,000
Specific Gravity		0.90
Color		Clear
Flash point	°C (°F)	-4 (25)
VOC Content ¹	g/L	855

¹Based on South Coast Air Quality Management District of California. Maximum VOC is listed both inclusive and exclusive of water and exempt compounds. For a VOC data sheet for a specific sealant color, please send your request to product.inquiry@dowcorning.com.

DESCRIPTION

Dow Corning[®] Primer C is a solvent-based silane adhesion promoter for use in construction applications for plastic and painted surfaces.

BENEFITS

Dow Corning Primer C has been shown to promote faster adhesion in low-temperature and low-humidity situations.

Other benefits can be determined in actual field installation and application tests.

HOW TO USE

Thoroughly clean surfaces to be primed by first brushing away any loose material and then wiping with an appropriate solvent on a coarse-free cloth. Wipe surfaces dry immediately

after cleaning. On nonporous substrates, *Dow Corning* Primer C should be applied with a lint-free cloth to maximize primer coverage rate and obtain a consistent thin film thickness. While a brush may be used to apply *Dow Corning* Primer C, the coverage rate will be lessened and it will be more difficult to obtain consistent film thickness.

Apply *Dow Corning* Primer C before the installation of backer rod in caulk joints. Allow the primer to dry for 20 minutes at room temperature or 1 hour at 5°C (41°F) before applying and tooling the sealant. Because this primer is a moisture-cure product, additional time is required for reaction before sealant application in cold temperatures. Refer to Dow Corning's published sealant installation guidelines for further information.

HANDLING PRECAUTIONS

Dow Corning Primer C is extremely flammable. Use caution when handling.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND MATERIAL SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE MATERIAL SAFETY DATA SHEET IS AVAILABLE ON THE DOW CORNING WEBSITE AT DOWCORNING.COM, OR FROM YOUR DOW CORNING SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CORNING CUSTOMER SERVICE.

USABLE LIFE AND STORAGE

Containers should be kept tightly sealed when not in use. When stored at or below 32°C (90°F) in the original unopened containers, *Dow Corning* Primer C has a usable life of 18 months from the date of manufacture.

PACKAGING INFORMATION

This product is available in various can sizes. Size availability varies by area. Please consult your local Dow Corning Sales Application Engineer for further information.

LIMITATIONS

Note: This primer will dissolve the expanded polystyrene (EPS) insulation board found within Exterior Insulation and Finish Systems (EIFS). Overapplication of this product onto EIFS substrates could diminish the integrity of the

substrate and void the EIFS Manufacturers Warranty.

Expired primer turns milky white.

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our Web site, dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

**DOW CORNING
SPECIFICALLY DISCLAIMS
ANY OTHER EXPRESS OR
IMPLIED WARRANTY OF
FITNESS FOR A
PARTICULAR PURPOSE OR
MERCHANTABILITY.**

**DOW CORNING DISCLAIMS
LIABILITY FOR ANY
INCIDENTAL OR
CONSEQUENTIAL DAMAGES.**

We help you invent the future.™

dowcorning.com